

Higher Quality
Better Service!

EXAM SELL

Certified IT practice exam authority

Accurate study guides, High passing rate!

Exam Sell provides update free of charge in
one year!



<http://www.examsell.com>

Exam : **350-801**

Title : Implementing and Operating
Cisco Collaboration Core
Technologies (CLCOR)

Version : DEMO

1.Refer to the exhibit.

```
voice translation-rule 1
rule 1 /^[2-9].....$/ /\0/ type any subscriber
rule 2 /^[2-9]..[2-9].....$/ /\0/ type any subscriber
```

What is the result of applying these two rules to a voice translation-profile for use with an ISDT1 PRI on a Cisco Voice gateway?

- A. The ISDN Type is modified to the administrators defined value.
- B. The ISDN Plan is modified to the administrators defined value.
- C. The leading Plus is stripped from the numeric phone number.
- D. Any Zero is stripped from the numeric phone number.

Answer: A

2.A network administrator deleted a user from the LDAP directory of a company. The end user shows as Inactive LDAP Synchronize User in Cisco Unified Communications Manager.

Which step is next to remove this user from Cisco Unified Communications Manager?

- A. Restart the Dirsync service after the user is deleted from LDAP directory.
- B. Delete the user directly from Cisco Unified Communications Manager.
- C. Wait 24 hours for the garbage collector to remove the user.
- D. Execute a manual sync to refresh the local databased and delete the end user.

Answer: C

3.A DTMS mismatch is occurring between an MGCP gateway registered FXS port and a Cisco Unified communications Manager SIP trunk.

Which media resource can be leveraged to interwork this mismatch?

- A. Media Termination point
- B. Conference Bridge
- C. Annunciator
- D. Trusted relay point

Answer: A

4.An engineer configures Cisco Unified Communications Manager to prevent toll fraud. At which two point does the engineer block the pattern in Cisco Unified CM to complete this task? (Choose two.)

- A. route pattern
- B. translation pattern
- C. route group
- D. partition
- E. CSS

Answer: D,E

5.How can an administrator stop Cisco Unified Communications Manager from advertising the OPUS codec for recording enabled devices?

- A. In CUCM Service Parameters set "Opus codec Enables" to "Enabled for all devices Except Recording-Enabled devices."
- B. Go to the phone's configuration page and set "Advertise OPUS Codec" to be "false"

- C. Router recorded calls through Cisco Unified Border Element because it does not support OPUS.
- D. Integrate the Cisco Unified CM with a recording solution that does not support OPUS.

Answer: A