

Higher Quality
Better Service!



Certified IT practice exam authority

Accurate study guides, High passing rate!

Exam Sell provides update free of charge in
one year!



<http://www.examsell.com>

Exam : HPE0-S54

**Title : Designing HPE Server
Solutions**

Version : DEMO

1.While installing a three frame Synergy solution, only two of the frames are identified during the discovery process.

What should you do to get resolution?

- A. Remove and re-insert the standby Composer
- B. Issue a refresh command to the enclosure
- C. Open the front panel of the Composer, and read the error message
- D. Validate Frame Link Module topology

Answer: D

2.What is required to enable Jitter Smoothing technology? (Choose two.)

- A. HPE Apollo
- B. ProLiant Gen 10
- C. HPE Synergy
- D. HPE Cloudline
- E. iLO5 Advanced

Answer: BE

3.A customer is using HPE Smart Update Manager (SUM) for firmware update. They plan to add 100 Gen10 ProLiant servers, and they are concerned about whether HPE SUM will be able to support this size of installation.

What other option could the customer use for firmware updates that has increased scalability?

- A. iLO Advanced Premium Security Edition
- B. Insight Control server provisioning
- C. Insight Cluster Management Utility
- D. iLO Amplifier Pack

Answer: D

4.A customer purchased HPE ProLiant Gen10 servers. The customer is transitioning from a physical to a virtual environment.

Which feature should be enabled to ensure that they get the optimal performance from their new servers?

- A. UEFI optimized boot
- B. Integration with an HPE OneView for VMware vCenter
- C. Performance optimization using the workload profiles
- D. OneView OS Build Plan

Answer: C

5.You want to form a Synergy management ring.

Which component is required?

- A. HPE Synergy Image Streamer
- B. HPE Synergy Frame Link Module
- C. HPE Synergy Composer
- D. HPE Synergy 10 Gb Interconnect Link Module

Answer: B